



TP 9200

The TP 9200 direct-to-card printer from Pointman delivers exceptional quality edge-to-edge printing. TP 9200 can print up to 200 single side cards or up to 155 dual side cards.



PRINTER ENCODING OPTIONS

Magnetic Stripe Encoding	ISO7811 (Track 1,2,3), Coercivity : HiCo/LoCo
Smart Card Personalization	ISO, EMV - Contact Landing Type
RF ID Card	Mifare, ISO 14443 A / B, ISO15693
SAM	PLCC 1 (Extra-2 Sockets), SIM 4 sockets

SPECIFICATIONS

Print Technology	Direct-to-card Dye-sublimation / Resin thermal transfer
Print Capabilities	One or Two Sided, edge-to-edge printing
	Full-color and monochrome printing capability
	Alphanumeric text, logos and digitized signatures
Print Resolution	300 dpi (11.8 dpm), 16.7 Million Color
Print Speed "Under specific condition"	Full-color Printing
	Single Side (YMCO) - up to 200 card/hr.
	Single Side (YMCKO) - up to 170 card/hr.
	Dual Side (YMCKO-K) - up to 155 cards /hr.
	Monochrome up to 550 cards/hr.
Card Capacity	Automatic Feed : 100-card input for 0.4mm ~1.2mm cards
	70-card output standard
	Manual Single Feed : 1-card input

PRINTER SPECIFICATIONS

Dimensions	Single : 403(L) × 192 (W) × 202 (H)mm
	Dual : 471(L) × 192 (W) × 202 (H)mm
Weight	Single : 5.5kg / Dual : 6.5kg
Power	100-240V ~ 50/60Hz 1.7A / Output : DC24V 3.75A
Font	True Type Fonts via Window Drivers
Memory	128MB RAM
Interface	USB2.0 (High-Speed), RS-232, Built in 10/100 Ethernet
Operation System for Printer Driver	All 32-bit, 64 bit compatible: Windows 8, Windows 7, Windows Vista, XP, Windows 2008 Server, Windows 2003 Server,
Approvals	FCC Class A, CE (EN 55022 Class A, EN 55024), CCC, KCC
Software	Card Designer™